

AUS40 is a mix of 40% urea in ultra-pure water. The product is injected in the exhaust of diesel and gas engine in order to reduce NOx emissions. Urea solution for the reduction of NOx in exhaust fumes.

Storage

AUS 40% needs to be stored in insulated stainless steel or plastic tanks.

Usage

Fill the special tank for AUS40, never add directly to the diesel.

UREA SOLUTION “AUS-40”

| | |
|------------------|--------------------------------------|
| Urea content | 40 % |
| Density | 20°C 11083 - 11142 kg/m ³ |
| Refractive index | 20°C 1.3932 – 1.3955 |
| Alkalinity | < 0,25 % (m/m) |
| Biuret | < 0,4 % (m/m) |
| Aldehydes | < 6,2 mg/kg |
| Insolubles | < 25 mg/kg |
| Phosphate | < 0,6 mg/kg |
| Aluminium | < 0,6 mg/kg |
| Calcium | < 0,6 mg/kg |
| Chromium | < 0,25 mg/kg |
| Iron | < 0,6 mg/kg |
| Potassium | < 0,6 mg/kg |
| Copper | < 0,25 mg/kg |
| Magnesium | < 0,6 mg/kg |
| Sodium | < 0,6 mg/kg |
| Nickel | < 0,25 mg/kg |
| Zinc | < 0,25 mg/kg |